

50 WBB 110 M05 W00

$V_{i\text{ nom}} = 72\text{V}, 110\text{V}$ $V_{O\text{ nom}} = 5\text{V}$ $I_{O\text{ nom}} = 10\text{A}$

SYMBOL	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input:						
V_{IN}	Input voltage range	Continuously	50.4		137.5	V_{DC}
$V_{IN\text{ Dyn}}$	Input voltage range dynamic	$V_{IN} = 43.2\text{V} \dots 50.4\text{V}$ for $t \leq 0.1\text{s}$ $V_{IN} = 137.5\text{V} \dots 154.0\text{V}$ for $t \leq 1\text{s}$	43.2		154.0	V_{DC} V_{DC}
$V_{IN\text{ Min}}$	Converter shutdown				65	V_{DC}
$V_{IN\text{ Max}}$	Converter shutdown		155			V
I_{IN}	Input current	no load			70	mA
		Nominal load	$V_{IN} = 154\text{V}, I_{OUT} = 0\text{A}$ $V_{IN} = 110\text{V}, I_{OUT} = 10\text{A}$	0.6		A
		Nominal load	$V_{IN} = 72\text{V}, I_{OUT} = 10\text{A}$ $V_{IN} = 43.2\text{V}, I_{OUT} = 10\text{A}$	0.9		A
			$V_{IN} = 154.0\text{V}$			1.5
	Input current integral				5	A^2s
$I_{IN\text{ Max}}$	Switch on current at $V_{IN} \geq V_{IN\text{ min}}$	$I_{OUT} = 10\text{A}$ $\Delta t \leq 200\text{ms}$			6	A
	Input Fuse		10 A Pico Fuse			
C_{IN}	Converter input capacitance			20	25	μF
	Max permitted external Line Inductance				25	μH
	Reverse input protection	parallel diode + input fuse	1.5 KE160A			

Output: Power Unit

$50.4\text{V} \leq V_{IN} \leq 137.5\text{V}$

$P_{OUT\text{ Nom}}$	Output power			50		W
$V_{OUT\text{ Nom}}$	Output voltage adjustment, factory set		+ 5.0	+ 5.1	+ 5.15	V
ΔV_{OUT}	Load regulation static	$0\text{A} \leq I_{OUT} \leq 10\text{A}$ $T_A = -40^\circ\text{C} \dots +70^\circ\text{C}$ $T_A = -40^\circ\text{C} \dots +85^\circ\text{C}$	$\pm 2.5\% V_{OUT\text{ nom}}$ $\pm 3.0\% V_{OUT\text{ nom}}$			
$\Delta V_{O\text{ dyn}}$	Load regulatin dynamic	Pulse load: 20 - 80 - 20 % x I_{OUT}		100	200	mV
t_{dyn}	Response time	Pulse load: 20 - 80 - 20 % x I_{OUT}		1	2	ms
$V_{O\text{ rms}}$	Ripple	Nominal load BW 300 kHz		75	150	mV
$V_{O\text{ pp}}$	Noise	Nominal load BW 20 MHz			200	mV
t_{on}	Turn on time V_o	$0\text{A} \leq I_{OUT} \leq 10\text{A}$ resistive load	25		200	ms
t_h	Hold Up Time Option: 10ms class S2 Recharge time: $t \leq 5\text{sec}$ @ $I_{out} \geq 1\text{A}$	$0\text{A} \leq I_{OUT} \leq 10\text{A}$	0			ms
	Oversvoltage Protection	$43.2\text{V} \leq V_{IN} \leq 154.0\text{V}$ $0\text{A} \leq I_{OUT} \leq 10\text{A}$	Transil Diode 1,5KE6.8A			
I_{OUT}	Output current			10		A
	Output current limitation		10.1			A
I_{AK}	Output short circuit current	short circuit between + V_o and - V_o $43.2\text{V} \leq V_{IN} \leq 154.0\text{V}$			15	A
	Sense Lines	No				
C_o	Converter Capacitance	Output		10		mF

Signals

Signals	Input	LED yellow
	Output	LED yellow

General Specifications

f	Switching frequency	$V_{IN} = 110\text{V}, I_{OUT} = 10\text{A}$		60		kHz
η	Efficiency	$P_{OUT} \geq 0.7 \times P_{OUT\text{ Nom}}$	80	83		%
	MTBF (SN 29500)	$V_{IN} = 110\text{V}, I_{OUT} = 10\text{A}, T_A = +40^\circ\text{C}$		500 000		h
	No load, short circuit proof		Continuously			

SYMBOL	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
SAFETY / DIMENSIONS						
	Creepage, Clearance for PD2 and OV2 PCB FR4 V0, TG = + 140°C	Input – Output Input – Case Output – Case	2.0 2.0 1.0			mm mm mm
	Converter Dielectric Strength Test each unit ramp function 2 s – 3 s – 2 s	Input – Output Input – Case Output – Case			2100 1500 750	V _{DC} V _{DC} V _{DC}
	Connector	Input, Output, SE: Combicon 5-pins Required femal plug:	DFK-MSTBA 2.5/5-GF-5.08 MSTB 2.5 HC/5-STF-5.08			
	Pin Assignment	Wire gauges	see drawing			
	Protection Class, Protection degree		I, IP 20			
	Dimensions see drawing	w x h x d	110 x 170 x 52			mm
	Assembling	Wall mounting with screws	4 x M4			
	Weight		650			g

ENVIRONMENTAL CONDITIONS

T _A	Operating Range	Continuously EN 50155 class Tx for 10 Min.	- 40 - 40		+ 70 + 85	°C °C
T _{Sto}	Storage Range		- 40		+ 85	°C
	Cooling		convection			
	Humidity	EN 50155, IEC 60571	75% averaged year, 95% 30 days			
	Vibration / Shock	IEC 61373, IEC 68-2-27, EN 50155 Cat. I 3 shocks each Axis	50 m / s ² , 30 ms			

EMV



	Emission	Line conducted and radiated	EN 50121 - 3 - 2: 2007			
	Immunity	ESD EN 61000 - 4 - 2	6 kV / 8 kV performance criteria - B -			
		High Frequency Field EN 61000 - 4 - 3	20 V / m 80 MHz ... 1 GHz performance criteria - A -			
		Burst EN 61000 - 4 - 4	Level 3 asym., sym. performance criteria - A -			
		Surge EN 61000 - 4 - 5	2 kV asym. / 1 kV sym. R _i = 42 Ω performance criteria - A -			
		HF – Current Injection EN 61000 - 4 - 6	10 V _{eff} , R _i = 150 Ω performance criteria - A -			

STANDARDS

Applied Standards:	EN 50155: 2008	BN 411 002	EN 50124 - 1: 2006	EN 50121 - 3 - 2: 2006	IEC 60571
	SN 29 500	EN 50 121 - 1	EN 50125 - 1	EN 60068 - 2 - 6, 2...27	EN 61000 - 4 - 2...6
	IEC 571	IEC 61373	EN 60721 - 3 - 5	EN 61373	EN 60529

Technical specifications valid for: - 40° C ≤ T_A ≤ + 70° C, 50.4 V ≤ V_{IN} ≤ 137.5 V, unless otherwise noted.

Dimensions (in mm) and pin assignment



View in direction of the arrow

Recommend wire gauges:

V_{in}: 1.0 mm²

V_{in}: 1.0 mm²

PE: 1.5 mm²

Order Key

W00	class S1 0ms
W01	class S2 10ms
W10	with mating connector, class S1
W11	with mating connector, classe S2